

ACCOYA FINGER JOINTED SPECIFICATION SHEET



KEY FEATURES



DIMENSIONALLY STABLE



OUTSTANDING DURABILITY



PERFECT FOR COATING

Accoya® wood is produced from sustainably sourced, fast growing wood and manufactured using Accsys' proprietary patented modification process from surface to core.



UV RESISTANT



NATURALLY INSULATING



EXCELLENT MACHINABILITY



INSECT BARRIER



CONSISTANT QUALITY THROUGHOUT



NATURALLY BEAUTIFUL WOOD



FROM SUSTAINABLE SOURCES



RETAINED STRENGTH & HARDNESS



NON-TOXIC & RECYCLABLE



ACCOYA FINGER JOINTED SPECIFICATION

Accoya finger jointed offers fixed width, engineered sections for joinery under the KOMO joinery certificate for finger joint quality. Accoya has been finger jointed under the KOMO scheme successfully since 2007, predominantly for the Dutch market.

Finger joint quality certification for opaque joinery use:



Cert. no. 33058/07
BRL 0605 Modified Timber
Accoya® is suitable for in use class 1, 2, 3 and 4 (EN 335-1)

DELIVERED SIZES

62 x 100	74 x 100
62 x 125	74 x 125
62 x 150	74 x 150
62 x 200	74 x 200

LENGTHS (10 M³ MINIMUM ORDER)

4,200
4,800
6,000
Custom (Max 6,000mm)

TOLERANCE

WIDTH	THICKNESS
-1mm / +3mm	+/- 0.5mm

